



DUST FREE – WALL PROTECTOR

Multiple-Layer Spray Booth Wall & Ceiling Protection Film

PRODUCT INFORMATION

DF-W-5-W/C-80 · V5 (07/26)

NOT A SPECK OF DUST

5+1 PEELABLE LAYERS

12 MONTHS

~120 MICRON

MADE IN EU

Patented multi-layer protection film for spray booth walls and ceilings. Each layer has a slightly tacky, statically charged surface that acts like a magnet for airborne dust and overspray – particles are captured at the wall before they reach the paintwork. When a layer is contaminated, peel it away in seconds to reveal a fresh charged surface beneath.

FEATURES & BENEFITS

FEATURE	BENEFIT
Tacky + electrostatically charged surface	Actively attracts and retains airborne dust and overspray
World-class multi-layer peel system	Peel one soiled layer in seconds – no full replacement, no downtime
Patented dispenser box with cutting bar	Installation in 50% less time; clean, accurate trimming; applicator included
Tape-free overlapping seam design	No edge tape required – and no re-taping after every peel
Colour-coded layer indicators	Know exactly how many layers remain at a glance
Embedded measuring tape in the roll	Calculate remaining roll length without unrolling
Innovative adhesive design	No adhesive residue on removal – booth surfaces stay clean
Temperature resistant up to 80°C	Insulates the booth and reduces bake time

Applications: Spray booth walls & ceilings · Mixing rooms · Paint mixing areas · Clean rooms



KEY SPECIFICATIONS

Product code	DF-W-5-W/C-80
Material	Polypropylene / polyester
Adhesive	Acrylic adhesive on both sides – water dilution varies by layer and side (low-tack capture face / mounting underside)
Colour	White or Transparent (clear)
Roll size	0.77 m × 80 m – covers ~60 m ² (standard EU booth)
Thickness	~120 micron
Layers	5 + 1 protective outer sheet (4-layer on request)
Layer life	~250 spray cycles or ~3 months, whichever comes first
Total lifespan	12 months per application